

Tube & Pipe Bending Machine

Additional Savings when Purchasing Tooling Kit with Machine

SB48 with Pipe Kit Part# SB48P

Pipe Size	CLR	Min. Wall	Center Former Part #	Counterbend Die Part #
1/2"	1.8	.109	153R046P0500	155P0500
3/4"	2.2	.113	153R056P0750	155P0750
1"	2.6	.133	153R067P1000	155P1000
11/4"	3.5	.140	153R090P1250	155P1250
11/2"	3.9	.145	153R100P1500	155P1500

Pipe Kit only Part# PIPEKIT2

SB48 with "Small Radius" Tube Kit Part# SB48TSR

Tube Size	CLR	Min. Wall	Center Former Part #	Counterbend Die Part #
3/4"	2.6	.035	153R067T0750	154T0750
7/8"	2.2	.065	153R056T0875	154T0875
1"	2.6	.065	153R067T1000	154T1000
11/4"	3.2	.083	153R082T1250	154T1250
11/2"	3.9	.083	153R100T1500	154T1500

[&]quot;Small Radius" Tube Kit only Part# TUBEKIT2SR

SB48 with "Large Radius" Tube Kit Part# SB48T

Tube Size	CLR	Min. Wall	Center Former Part#	Counterbend Die Part#
3/4"	2.6	.035	153R067T0750	154T0750
7/8"	2.6	.035	153R067T0875	154T0875
1"	3.2	.035	153R082T1000	154T1000
11/4"	4.4	.035	153R112T1250	154T1250
11/2"	5.9	.049	153R150T1500	154T1500
13/4"	6.7	.065	153R170T1750	154T1750

"Large Radius" Tube Kit only Part# TUBEKIT2



Store Multiple Bend Angles and Programs

FEATURES

- Ideal for producing consistent quality bends in pipe, tube, squares, solids and other profiles
- Touch screen programming of bend angle with system diagnostics in multiple languages
- Touch screen indicates digital display of bend angle, springback and bend speed for each angle within the program
- Bend any angle to 180° with independent material springback compensation for each bend

- Quick-change tooling system with multiple radii available
- Patented swing away counter bend die vise offers easy loading and unloading of work piece, monitored electronically for greater accuracy
- Automatically stops at desired bend angle to end cycle
- Use control panel or foot pedal to initiate bend and return functions
- Counterbending die position monitored electronically for accuracy and repeatability

SB48 Capacities & Specifications

Tube	(Min.) (Max.)		1/4" 2"
Pipe	(Max.)		1½" Sch. 40
Cente	erline Radius	(Min.) (Max.)	2 x Ø 8%"
Degre	ee of Bend		0-210°
Bendi	ng Speed		Variable
Progr	amming		Touch screen Program storage Multiple bends per program
	amming ial Positionin	g Table	Program storage
	ial Positionin	g Table	Program storage Multiple bends per program
Mater Voltaç	ial Positionin		Program storage Multiple bends per program Available (see page 30)

All capacities based on A53 grade A 48,000 psi tensile materials; heavy wall and high tensile materials reduce machine capacity. Consult supplier for material specifications.

POPULAR ACCESSORIES



Tube & Pipe Tooling Kits





Two Axis Positioner



Easy Part Layout Software



Square Tooling

Tooling Kits Pages 15-16

Tooling and **Accessories Pages 17-31**

Model Comparison Guide Page 36

- No hydraulic components
- Accepts Ercolina's A40-P two axis positioning table for multiple and sequential bends
- Classic Ercolina Super Bender design reduces floor space requirement and stores easily to save shop floor space
- Individual tooling available on pages 15-29

Product Demonstrations Available on Website

NEED ADDITIONAL HELP? CONTACT ERCOLINA:

563.391.7700

info@ercolina-usa.com